

KENWOOD

Listen to the Future

NEXEDGE™

NXR-700/800

NEXEDGE™ VHF/UHF Digital & FM Base Units

NXDN®

● GENERAL FEATURES

- 136-154, 146-174 MHz
- 400-430, 450-480, 480-512 MHz
- 40 / 100 / 250 Watt UHF Systems
- Repeater Operation
- Duplex / Simplex Base Operation
- 30 CH Scanning Base (Conventional)
- Two-Digit LED Display
- LED Status Indicators
- 6 Programmable Function Keys
- 3 W External Speaker Audio
- Volume Control
- Microphone Jack
- Program / Modem Interface
- Remote Termination Interface
- Programmable AUX I/O's
- DTMF Front Panel PF Key Control
- DTMF AUX Output Control
- DTMF AUX Input Monitoring
- KPG-109D Windows® FPU
- Flash Firmware Upgrading

● DIGITAL – GENERAL

- NXDN® Digital Air Interface
- NXDN® Scrambler Included
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- UID & GID Validation
- NXR Over-the-Air Alias
- KXX-3 OCXO Option

● DIGITAL – CONVENTIONAL MODE

- 16 RAN Repeater Controller Built-in
- 1,000 GIDs Per Site
- 1,000 UIDs Per Site
- Mixed FM/Digital Operation

● DIGITAL TRUNKING OPTION

- 3,000 GIDs Per Site
- 3,000 UIDs Per Site
- 30 Channels Per Site
- Transmission Trunked Mode
- Message Trunked Mode
- Busy Call Queuing
- Call Que Pre-emption
- Late Entry (UID & GID)
- Control / Traffic Channel Switching
- Control Channel Rotation
- Cross-Busy
- Failsoft Mode
- NXDN® Traffic Channel Sharing
- 2MB Call/Activity Memory
- Compact Flash Memory Expansion

● MULTI-SITE IP NETWORK OPTION

- 16 Site Trunked IP Network
- 60,000 GIDs Per Network
- 60,000 UIDs Per Network
- NEXEDGE™ Trunked Features
- Ethernet Network Interface
- IP LAN/WAN Connectivity
- ESN Validation
- Auto-Roaming / Registration
- Wide Area All Group Call
- Virtual Private Network
- Group Registration
- Use of Off-the-Shelf 10 Base-T/100 Base-TX Ethernet Switching & Routers

● KPG-110SM SYSTEM MANAGER

- Trunked Sites & IP Network Systems Only
- Windows® 2000/XP/Vista® Compatible
- USB Secure Key Access
- Direct, Dial-Up & IP Connectivity
- Subscriber Privileging
- 127 UID Class-of-Service Entries
- 127 GID Class-of-Service Entries
- 5000 Fleets (UID/GID User Lists)
- Group Call Inter-Site Limits
- Remote Site Programming
- Real-Time Activity Monitoring
- NXR/Network Interface Diagnostics
- Call Logging / Event Download
- Remote System Firmware Updates

● FM MODES – GENERAL

- 25 & 12.5 kHz Channels
- Encryption/ANI Board Control

● FM CONVENTIONAL MODE

- 16 QT/DQT Repeater Control Built-in
- Hang Timer / Time Out Timer / CW ID
- External FM Controller Interface
- EIA Voter Tone Generation

● FM TRUNKED MODE

- External LTR® Controller Interface
- External MPT Controller Interface



Options

■ **KXK-3***
OCXO Unit



■ **KMC-35**
Microphone



■ **KES-5**
External Speaker



■ **KMC-30**
Microphone



■ **KMC-9C**
Desktop Microphone



* Required for 6.25 kHz trunking or frequency stability to observe the regulations.

All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

		NXR-700	NXR-800
GENERAL			
Frequency Range	K K2 K3	146-174 MHz 136-154 MHz	450-480 MHz 480-512 MHz (RX) / 477-512 MHz (TX) 400-430 MHz
Channel Spacing	Analog Digital	12.5 / 15 / 25 / 30 kHz 6.25 / 12.5 kHz	12.5 / 25 kHz 6.25 / 12.5 kHz
PLL Channel Step		2.5 / 3.125 / 5 / 6.25 kHz	3.125 / 5 / 6.25 kHz
Frequency Stability	With KXK-3 (M) With KXK-3 (M2)		± 1.5 ppm ± 0.5 ppm ± 1.0 ppm
Operating Voltage			10.8 - 15.9 V DC
Operating Temperature Range			-30° C to +60° C (-22° F to + 140° F)
Antenna Impedance			50 Ω
Dimensions (W x H x D)	Projections not included		483 x 44 x 331 mm
Weight (net)			5 kg
RECEIVER			
Sensitivity	Digital @ 6.25kHz (3% BER) Digital @ 12.5kHz (3% BER) Analog (12 dB SINAD)		0.27 μV 0.33 μV 0.30 μV
Selectivity	Analog @ 25/30 kHz Analog @ 12.5 kHz	93 dB (± 30 kHz) 85 dB (± 12.5 kHz)	87 dB (± 25 kHz) 81 dB (± 12.5 kHz)
FM Hum & Noise	Analog @ 25/30 kHz Analog @ 12.5 kHz		60 dB 55 dB
Intermodulation Distortion			85 dB (± 50 / 100 kHz)
Spurious Response			100 dB
Audio Distortion (Ext. SP)			Less than 2% (at 0.3 W)
Audio Output (Ext. SP)			3 W (at 4Ω, less than 5% distortion)
TRANSMITTER			
RF Power Output			5 W to 0.5 W
Spurious & Harmonics			73 dB
FM Hum & Noise	Analog @ 25/30 kHz Analog @ 12.5 kHz		55 dB 50 dB
Audio Distortion			Less than 1% at 1000 Hz
Modulation			16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D

Analog measurements made per TIA/EIA 603 and specifications shown are typical.
Kenwood reserves the right to change specifications without prior notice or obligation.

LTR® is a registered trademark of Transcript International.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
Windows® and Windows 2000/XP/Vista® are registered trademarks of Microsoft Corporation.
NXDN® is a registered trademark of Kenwood Corporation and Icom Inc.
NEXEDGE™ is a trademark of Kenwood Corporation in U.S.A. and some countries.

Listen to the Future

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

Kenwood Corporation

1-16-2 Hakusan, Midori-ku, Yokohama-shi, Kanagawa, 226-8525 Japan

www.kenwood.com

http://nexedge.kenwood.com

